

L Number	Hits	Search Text	DB	Time stamp
-	262	(rout\$6 with (parameter or QoS or characteristic)) and,PPP and 370/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/21 07:33
-	8	((multiple with PPP) same ((single or "same") near3 address)) and 370/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:45
-	58	((PPP or (point near2 point)) with (connection or link or session or channel) with (multiple or multi or many or plurality)) same (address with (single or "same" or one))) and 370/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:58
-	117	((PPP or (point near2 point)) with (connection or link or session or channel) with (multiple or multi or many or plurality)) same (address with (single or "same" or one)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 09:05
-	91	((connection or link or session or channel) near3 (multiple or multi or many or plurality)) with (address near3 (single or "same" or one)).ab.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 09:10
-	183	((connection or link or session or channel) near3 (multiple or multi or many or plurality)) with (address near3 (single or "same" or one))) and 370/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 09:27
-	25	(PPP same address same QoS) and 370/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 09:28
-	9	("5557798" "5717689" "5757783" "5822309" "6049549" "6222820" "6223222" "6286052" "6330316").PN.	USPAT	2004/09/20 09:34
-	17	("5311513" "5497371" "5684791" "5745380" "5771459" "5787080" "5956341" "5970062" "6011776" "6023456" "6026082" "6084888" "6157614" "6188670" "6412006" "6477141" "6487212").PN.	USPAT	2004/09/20 09:43
-	7	("5822319" "5987022" "6189033" "6253326" "6295532" "6415313" "6466985").PN.	USPAT	2004/09/20 09:57

-	29	PPP and CDMA and PDSN and IPCP and 370/\$.cccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 12:27
-	53	PPP and CDMA and PDSN and (compression or encrypt\$6) and 370/\$.cccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 12:37
-	104	PPP and CDMA and (encrypt\$6) and 370/\$.cccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 15:34
-	57	(PPP same encrypt\$6) and 370/\$.cccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 15:34
-	94	IPCP and (configuration with option)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/21 07:34

Network Working Group
Request for Comments: 1332
Obsoletes: RFC 1172

G. McGregor
Merit
May 1992

The PPP Internet Protocol Control Protocol (IPCP)

Status of this Memo

This RFC specifies an IAB standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "IAB Official Protocol Standards" for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Abstract

The Point-to-Point Protocol (PPP) [1] provides a standard method of encapsulating Network Layer protocol information over point-to-point links. PPP also defines an extensible Link Control Protocol, and proposes a family of Network Control Protocols (NCPs) for establishing and configuring different network-layer protocols.

This document defines the NCP for establishing and configuring the Internet Protocol [2] over PPP, and a method to negotiate and use Van Jacobson TCP/IP header compression [3] with PPP.

This RFC is a product of the Point-to-Point Protocol Working Group of the Internet Engineering Task Force (IETF).

McGregor
□
RFC 1332

PPP IPCP

[Page i]
May 1992

Table of Contents

1.	Introduction	1
2.	A PPP Network Control Protocol (NCP) for IP	2
2.1	Sending IP Datagrams	2
3.	IPCP Configuration Options	4
3.1	IP-Addresses	5
3.2	IP-Compression-Protocol	6
3.3	IP-Address	8
4.	Van Jacobson TCP/IP header compression	9
4.1	Configuration Option Format	9
	APPENDICES	11
A.	IPCP Recommended Options	11
	SECURITY CONSIDERATIONS	11
	REFERENCES	11
	ACKNOWLEDGEMENTS	11
	CHAIR'S ADDRESS	12
	AUTHOR'S ADDRESS	12

McGregor

[Page ii]

□

RFC 1332

PPP IPCP

May 1992

1. Introduction

PPP has three main components:

1. A method for encapsulating datagrams over serial links.
2. A Link Control Protocol (LCP) for establishing, configuring, and testing the data-link connection.
3. A family of Network Control Protocols (NCPs) for establishing and configuring different network-layer protocols.

In order to establish communications over a point-to-point link, each end of the PPP link must first send LCP packets to configure and test the data link. After the link has been established and optional facilities have been negotiated as needed by the LCP, PPP must send NCP packets to choose and configure one or more network-layer protocols. Once each of the chosen network-layer protocols has been configured, datagrams from each network-layer protocol can be sent over the link.

The link will remain configured for communications until explicit LCP or NCP packets close the link down, or until some external event occurs (an inactivity timer expires or network administrator intervention).

McGregor

[Page 1]

□

RFC 1332

PPP IPCP

May 1992

2. A PPP Network Control Protocol (NCP) for IP

The IP Control Protocol (IPCP) is responsible for configuring, enabling, and disabling the IP protocol modules on both ends of the point-to-point link. IPCP uses the same packet exchange mechanism as the Link Control Protocol (LCP). IPCP packets may not be exchanged until PPP has reached the Network-Layer Protocol phase. IPCP packets received before this phase is reached should be silently discarded.

The IP Control Protocol is exactly the same as the Link Control Protocol [1] with the following exceptions:

Data Link Layer Protocol Field

Exactly one IPCP packet is encapsulated in the Information field of PPP Data Link Layer frames where the Protocol field indicates type hex 8021 (IP Control Protocol).

Code field

Only Codes 1 through 7 (Configure-Request, Configure-Ack, Configure-Nak, Configure-Reject, Terminate-Request, Terminate-Ack and Code-Reject) are used. Other Codes should be treated as unrecognized and should result in Code-Rejects.

Timeouts

IPCP packets may not be exchanged until PPP has reached the Network-Layer Protocol phase. An implementation should be prepared to wait for Authentication and Link Quality Determination to finish before timing out waiting for a Configure-Ack or other response. It is suggested that an implementation give up only after user intervention or a configurable amount of time.

Configuration Option Types

IPCP has a distinct set of Configuration Options, which are defined below.

2.1. Sending IP Datagrams

Before any IP packets may be communicated, PPP must reach the Network-Layer Protocol phase, and the IP Control Protocol must reach the Opened state.

Exactly one IP packet is encapsulated in the Information field of PPP Data Link Layer frames where the Protocol field indicates type hex 0021 (Internet Protocol).

McGregor

[Page 2]

□

RFC 1332

PPP IPCP

May 1992

The maximum length of an IP packet transmitted over a PPP link is the same as the maximum length of the Information field of a PPP data link layer frame. Larger IP datagrams must be fragmented as necessary. If a system wishes to avoid fragmentation and reassembly, it should use the TCP Maximum Segment Size option [4], and MTU discovery [5].

McGregor

[Page 3]

□

RFC 1332

PPP IPCP

May 1992

3. IPCP Configuration Options

IPCP Configuration Options allow negotiation of desirable Internet Protocol parameters. IPCP uses the same Configuration Option format defined for LCP [1], with a separate set of Options.

The most up-to-date values of the IPCP Option Type field are specified in the most recent "Assigned Numbers" RFC [6]. Current values are assigned as follows:

- | | |
|---|-------------------------|
| 1 | IP-Addresses |
| 2 | IP-Compression-Protocol |
| 3 | IP-Address |

McGregor

[Page 4]

□

RFC 1332

PPP IPCP

May 1992

3.1. IP-Addresses

Description

The use of the Configuration Option IP-Addresses has been deprecated. It has been determined through implementation experience that it is difficult to ensure negotiation convergence in all cases using this option. RFC 1172 [7] provides information for implementations requiring backwards compatability. The IP-Address Configuration Option replaces this option, and its use is preferred.

This option SHOULD NOT be sent in a Configure-Request if a Configure-Request has been received which includes either an IP-Addresses or IP-Address option. This option MAY be sent if a Configure-Reject is received for the IP-Address option, or a Configure-Nak is received with an IP-Addresses option as an appended option.

Support for this option MAY be removed after the IPCP protocol

status advances to Internet Draft Standard.

McGregor

[Page 5]

□

RFC 1332

PPP IPCP

May 1992

3.2. IP-Compression-Protocol

Description

This Configuration Option provides a way to negotiate the use of a specific compression protocol. By default, compression is not enabled.

A summary of the IP-Compression-Protocol Configuration Option format is shown below. The fields are transmitted from left to right.

```

0           1           2           3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |   IP-Compression-Protocol   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Data ...
+---+---+---+

```

Type

2

Length

>= 4

IP-Compression-Protocol

The IP-Compression-Protocol field is two octets and indicates the compression protocol desired. Values for this field are always the same as the PPP Data Link Layer Protocol field values for that same compression protocol.

The most up-to-date values of the IP-Compression-Protocol field are specified in the most recent "Assigned Numbers" RFC [6]. Current values are assigned as follows:

Value (in hex)	Protocol
002d	Van Jacobson Compressed TCP/IP

Data

The Data field is zero or more octets and contains additional data as determined by the particular compression protocol.

McGregor

[Page 6]

□

RFC 1332

PPP IPCP

May 1992

Default

No compression protocol enabled.

McGregor

[Page 7]

□

RFC 1332

PPP IPCP

May 1992

3.3. IP-Address

Description

This Configuration Option provides a way to negotiate the IP address to be used on the local end of the link. It allows the sender of the Configure-Request to state which IP-address is desired, or to request that the peer provide the information. The peer can provide this information by NAKing the option, and returning a valid IP-address.

If negotiation about the remote IP-address is required, and the peer did not provide the option in its Configure-Request, the option SHOULD be appended to a Configure-Nak. The value of the IP-address given must be acceptable as the remote IP-address, or indicate a request that the peer provide the information.

By default, no IP address is assigned.

A summary of the IP-Address Configuration Option format is shown below. The fields are transmitted from left to right.

```

0           1           2           3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |   IP-Address   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   IP-Address (cont)   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

3

Length

6

IP-Address

The four octet IP-Address is the desired local address of the sender of a Configure-Request. If all four octets are set to zero, it indicates a request that the peer provide the IP-Address information.

Default

No IP address is assigned.

McGregor

[Page 8]

RFC 1332

PPP IPCP

May 1992

4. Van Jacobson TCP/IP header compression

Van Jacobson TCP/IP header compression reduces the size of the TCP/IP headers to as few as three bytes. This can be a significant improvement on slow serial lines, particularly for interactive traffic.

The IP-Compression-Protocol Configuration Option is used to indicate the ability to receive compressed packets. Each end of the link must separately request this option if bi-directional compression is desired.

The PPP Protocol field is set to the following values when transmitting IP packets:

Value (in hex)

0021 Type IP. The IP protocol is not TCP, or the packet is a
fragment, or cannot be compressed.

002d Compressed TCP. The TCP/IP headers are replaced by the compressed header.

002f Uncompressed TCP. The IP protocol field is replaced by the slot identifier.

4.1. Configuration Option Format

A summary of the IP-Compression-Protocol Configuration Option format to negotiate Van Jacobson TCP/IP header compression is shown below. The fields are transmitted from left to right.

0										1										2										3											
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
Type										Length										IP-Compression-Protocol																					
Max-Slot-Id										Comp-Slot-Id																															

```

+---+---+---+---+---+---+---+---+---+

```

Type

2

Length

6

McGregor

[Page 9]

□

RFC 1332

PPP IPCP

May 1992

IP-Compression-Protocol

002d (hex) for Van Jacobson Compressed TCP/IP headers.

Max-Slot-Id

The Max-Slot-Id field is one octet and indicates the maximum slot identifier. This is one less than the actual number of slots; the slot identifier has values from zero to Max-Slot-Id.

Note: There may be implementations that have problems with only one slot (Max-Slot-Id = 0). See the discussion in reference [3]. The example implementation in [3] will only work with 3 through 254 slots.

Comp-Slot-Id

The Comp-Slot-Id field is one octet and indicates whether the slot identifier field may be compressed.

0 The slot identifier must not be compressed. All compressed TCP packets must set the C bit in every change mask, and must include the slot identifier.

1 The slot identifier may be compressed.

The slot identifier must not be compressed if there is no ability for the PPP link level to indicate an error in reception to the decompression module. Synchronization after errors depends on receiving a packet with the slot identifier. See the discussion in reference [3].

McGregor

[Page 10]

□

RFC 1332

PPP IPCP

May 1992

A. IPCP Recommended Options

The following Configurations Options are recommended:

IP-Compression-Protocol -- with at least 4 slots, usually 16 slots.

IP-Address -- only on dial-up lines.

Security Considerations

Security issues are not discussed in this memo.

References

- [1] Simpson, W., "The Point-to-Point Protocol", RFC 1331, May 1992.
- [2] Postel, J., "Internet Protocol", RFC 791, USC/Information Sciences Institute, September 1981.
- [3] Jacobson, V., "Compressing TCP/IP Headers", RFC 1144, January 1990.
- [4] Postel, J., "The TCP Maximum Segment Size Option and Related Topics", RFC 879, USC/Information Sciences Institute, November 1983.
- [5] Mogul, J., and S. Deering, "Path MTU Discovery", RFC 1191, November 1990.
- [6] Reynolds, J., and J. Postel, "Assigned Numbers", RFC 1060, USC/Information Sciences Institute, March 1990.
- [7] Perkins, D., and R. Hobby, "Point-to-Point Protocol (PPP) initial configuration options", RFC 1172, August 1990.

Acknowledgments

Some of the text in this document is taken from RFCs 1171 & 1172, by Drew Perkins of Carnegie Mellon University, and by Russ Hobby of the University of California at Davis.

Information leading to the expanded IP-Compression option provided by Van Jacobson at SIGCOMM '90.

McGregor

[Page 11]

□

RFC 1332

PPP IPCP

May 1992

Bill Simpson helped with the document formatting.

Chair's Address

The working group can be contacted via the current chair:

Brian Lloyd
Lloyd & Associates
3420 Sudbury Road
Cameron Park, California 95682

Phone: (916) 676-1147

EMail: brian@ray.lloyd.com

Author's Address

Questions about this memo can also be directed to:

Glenn McGregor
Merit Network, Inc.
1071 Beal Avenue
Ann Arbor, MI 48109-2103

Phone: (313) 763-1203

EMail: Glenn.McGregor@Merit.edu

McGregor
□

[Page 12]